

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 May 2005 (06.05.2005)

PCT

(10) International Publication Number
WO 2005/041438 A1

(51) International Patent Classification⁷: **H04B 7/005,**
H03G 3/30, 3/20

(21) International Application Number:
PCT/EP2004/010031

(22) International Filing Date:
8 September 2004 (08.09.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
03024457.8 23 October 2003 (23.10.2003) EP

(71) Applicant (for all designated States except US): SONY
ERICSSON MOBILE COMMUNICATIONS AB
[SE/SE]; Nya Vattentomet, S-221 88 Lund (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): ITKIN, Grigory
[DE/DE]; Eduard-Schmidt-Str. 17, 81541 Munich (DE).
KABANOV, Andrei [RU/DE]; Bruno-Walter Ring 32,
81927 München (DE).

(74) Agents: RUPP, Christian et al.; Mitscherlich & Partner,
Sonnenstrasse 33, Postfach 33 06 09, 80066 München
(DE).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: ADDITIONAL REGULATION OF THE REFERENCE SIGNAL OF THE AUTOMATIC POWER CONTROL IN A MOBILE TERMINAL



(57) Abstract: The present invention generally relates to the field of automatic power control (APC) circuitries used in the analog front end of a mobile transmitter. It particularly refers to a power control circuitry (101M, 101N) and a corresponding method for controlling the power level (P_{out}) of an RF signal ($x(t)$) to be transmitted at the output port of a variable-gain power amplifier (105) by performing an additional regulation of the APC loop's reference signal (V_{ref}). Thereby, it is proposed to increase the radiated RF power (P_{out}) in case a transmitting antenna (110) is mismatched to said power amplifier (105) in order to not release an ongoing call. In case there is a subject very close to the terminal antenna, the antenna load is changed and the increased reflected signal is measured. In a closed loop this increased reflected signal is mixed with a reference ramp signal (V_{ramp}) which is used to calculate (S1A) a reference signal (V_{ref}) representing the nominal power level (P_{ref}) for the power (P_{out}) of the RF signal ($x(t)$) to be transmitted, which leads to an increasing of the radiated power and prevents said call from being released. The step of calculating (S1A) the reference signal (V_{ref}) as a function of the reference ramp signal (V_{ramp}) and a DC feedback signal (V_{PD}) is realized by the substeps of multiplying (S1a') a processed version ($K \cdot G_{OP} \cdot V_{PD}$) of the DC feedback signal (V_{PD}) by the reference ramp signal (V_{ramp}) and adding (S1a'') the output signal ($V_{ramp} \cdot K \cdot G_{OP} \cdot V_{PD}$) of the multiplication step (S1a') to the reference ramp signal (V_{ramp}), thereby yielding said reference signal (V_{ref}).

BEST AVAILABLE COPY



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.